

## UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
09/408,921	09/30/1999	ANTHONY J. RICCI	LAM1P118	4619
22434 7:	590 04/22/2004		EXAMINER	
BEYER WEAVER & THOMAS LLP			BUEKER, RICHARD R	
P.O. BOX 778 BERKELEY.	CA 94704-0778		ART UNIT PAPER NUMBER	
DERREEDI,			1763	
			DATE MAILED: 04/22/2004	4

Please find below and/or attached an Office communication concerning this application or proceeding.

`	Application No.	Applicant(s)	
	09/408,921	RICCI ET AL.	
Office Action Summary	Examiner	Art Unit	
	Richard Bueker	1763	
The MAILING DATE of this communication Period for Reply	n appears on the cover sheet wit	h the correspondence address	
A SHORTENED STATUTORY PERIOD FOR R THE MAILING DATE OF THIS COMMUNICATION  - Extensions of time may be available under the provisions of 37 CI after SIX (6) MONTHS from the mailing date of this communication  - If the period for reply specified above is less than thirty (30) days,  - If NO period for reply is specified above, the maximum statutory p  - Failure to reply within the set or extended period for reply will, by any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	ON. FR 1.136(a). In no event, however, may a rein. a reply within the statutory minimum of thirty eriod will apply and will expire SIX (6) MONT statute, cause the application to become ABA	ply be timely filed  (30) days will be considered timely.  THS from the mailing date of this communication  ANDONED (35 U.S.C. § 133).	ation.
Status			
1) Responsive to communication(s) filed on	20 January 2004.		
	This action is non-final.		
3) Since this application is in condition for all closed in accordance with the practice unc	owance except for formal matte	• •	s is
Disposition of Claims			
<ul> <li>4)  Claim(s) 1,2,4-7,11-14,18,40 and 43-45 is 4a) Of the above claim(s) is/are with 5)  Claim(s) is/are allowed.</li> <li>6)  Claim(s) 1,2,4-7,11-14,18,40 and 43-45 is 7)  Claim(s) is/are objected to.</li> <li>8)  Claim(s) are subject to restriction and an are subject to restriction and an are subject.</li> </ul>	ndrawn from consideration.  /are rejected.		
Application Papers			
9) The specification is objected to by the Exa	miner.		
10) The drawing(s) filed on is/are: a)	accepted or b) ☐ objected to b	y the Examiner.	
Applicant may not request that any objection to	o the drawing(s) be held in abeyand	ce. See 37 CFR 1.85(a).	
Replacement drawing sheet(s) including the control of the oath or declaration is objected to by the	• - •		• •
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for for a) All b) Some * c) None of:  1. Certified copies of the priority docur 2. Certified copies of the priority docur 3. Copies of the certified copies of the application from the International But * See the attached detailed Office action for a	ments have been received. ments have been received in Ap priority documents have been ureau (PCT Rule 17.2(a)).	oplication No received in this National Stage	
Attachment(s)  1) ☑ Notice of References Cited (PTO-892)	A) ☐ Imeandarin Co	ummary (PTO 442)	
1) 🔯 Notice of References Cited (PTO-892) 2) 🔲 Notice of Draftsperson's Patent Drawing Review (PTO-948	Paper No(s)	ummary (PTO-413) /Mail Date	
<ol> <li>Information Disclosure Statement(s) (PTO-1449 or PTO/SI Paper No(s)/Mail Date</li> </ol>		formal Patent Application (PTO-152) 	

Art Unit: 1763

Claims 18 and 44 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. In claims 18 and 44, the phrase "where a second machining of only ceramic surfaces that are not exposed to plasma is performed after the annealing process" is new matter. In particular the phrase "only ceramic surfaces that are not exposed to plasma" was not in the specification as originally filed.

Claims 1, 2, 4-7, 11, 44 and 45 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. In claim 1, the phrase "the micro-defects" lacks proper antecedent basis.

Claims 12-14, 18 and 43 are rejected under 35 U.S.C. 103(a) as being unpatentable over Maydan (5,746,875) taken in view of Aihara I (U.S. 6,258,440) or Aihara II (JP 10-167859). Maydan discloses a plasma-based fabrication apparatus that includes a ceramic gas distribution plate (GDP) having a plurality of holes that supply plasma gases. Maydan's GDP has a machined surface. Maydan teaches that it should be pre-treated to reduce particulates but does not discuss annealing for reducing undesirable particulates. Aihara (I and II) teaches that a ceramic part having a machined surface that is intended to be used in a plasma based fabrication apparatus should be annealed after the ceramic part is machined. Aihara teaches that this annealing step will eliminate the undesirable particulates that are otherwise produced

Art Unit: 1763

when the ceramic part is used in the plasma-based fabrication apparatus. Aihara specifically teaches (col. 5, line 9) that his annealing step is applicable to a shower plate, which is a GDP. Aihara's annealing temperature is within the range recited in applicants' claim 12 (see, for example, Invention Examples 3 and 4 at col. 6, lines 16-53 of Aihara). It would have been obvious to one skilled in the art to anneal the ceramic GDP of Maydan in the manner taught by Aihara, because Aihara teaches that his annealing process will help to eliminate the particles that that Maydan desires to eliminate.

Regarding the citation of both Aihara documents in the above rejection, it is noted that Aihara II (JP 10-167859) is the Japanese language priority document for Aihara I (U.S. 6,258,440). Aihara I has a typographical error at col. 7, line 34, in the section labeled "Invention Example 6", where the reference to "Comparative Example 1" should be "Comparative Example 2". The original Japanese language priority document (translation attached) makes this clear. Thus, it is clear that "Invention Example 6" of Aihara is directed to the Aluminum Nitride embodiment disclosed by Aihara. This is the reason for including a citation of JP 10-167859 in the rejection.

Claims 12-14 and 40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Herchen (5,819,434) taken in view of Aihara I (6,258,440) or Aihara II (JP 10-167859). Herchen (see Figs. 3 and 4, and col.5, lines 11-18) discloses a ceramic GDP for use in a plasma-based fabrication apparatus, that is formed by machining, which includes a machined surface through which a plurality of holes pass. It would have been obvious to one skilled in the art to subject the ceramic GDP of Herchen to an

Art Unit: 1763

annealing treatment after machining, as taught by Aihara I and II, for the desirable purpose of reducing the generation of particles when the GDP is used in a plasmabased fabrication apparatus. Regarding the recitation of drilled holes in claims 1 and 40, it is noted that this is a product-by-process limitation that is not structurally distinguishable from the holes of Herchen's GDP.

Claim 40 is rejected under 35 U.S.C. 103(a) as being unpatentable over Herchen (5,819,434) taken in view of Aihara I (6,258,440) or Aihara II (JP 10-167859) for the reasons stated above, taken in further view of Maydan (5,746,875) (col. 2, lines 3-4) and Chen (5,824,605) (col. 8, lines 8-17), who teach that it was conventional in the prior art to drill the gas distribution holes in a ceramic GDP. It would have been obvious to one skilled in the art to drill Herchen's holes, because Maydan and Chen teach that it was known in the art to form GDP holes by drilling.

Claims 1, 2, 4-7, 11, 18 and 43-45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Herchen (5,819,434) taken in view of Aihara I (6,258,440) for the reasons discussed in the rejection of claims 12-14 and 40 above, and taken in further view of Maydan or Wicker III (WO 98/14980) or Kim (6,041,733), and in further view of Aihara III (6,099,794) and Takahashi (JP 60-81076). Claims 1, 2, 4-7, 11 and 43-45 are now limited to a GDP including at least one of Si<sub>3</sub>N<sub>4</sub> and SiC. The GDP of Herchen's preferred embodiment is constructed of aluminum oxide, but Herchen (col. 5, lines 1-10) also teaches that the particular material used to fabricate the GDP is determined largely by the chemical resistance required for a particular process chemistry. Herchen teaches that other ceramics can be used as appropriate for the process chemistries

Art Unit: 1763

involved. Maydan (col. 6, lines 17-20) and Wicker III (paragraph bridging pages 10 and 11) both teach that Si₃N₄ is a desirable material of construction for a ceramic GDP, and Kim (Figs. 4 and 5 and col. 3, lines 63-66) teaches that SiC is a desirable material of construction for a GDP. In view of Maydan or Wicker III or Kim, it would have been obvious to use Si<sub>3</sub>N<sub>4</sub> or SiC as the material of construction for Herchen's ceramic GDP. Regarding a step of annealing a Si<sub>3</sub>N<sub>4</sub> or SiC GDP, Aihara I (col. 4, lines 7-18) and Takahashi (see the English translation) teach that it is desirable to anneal a Si<sub>3</sub>N<sub>4</sub> or SiC article to improve its strength, and Aihara III (col. 4, lines 51-64) teaches that it is desirable to anneal a Si<sub>3</sub>N<sub>4</sub> article to improve its strength. It would have been obvious to one skilled in the art to anneal a GDP made of Si<sub>3</sub>N<sub>4</sub> or SiC as suggested by Maydan or Wicker III or Kim because strength is a desirable feature in any ceramic article. Also, Herchen (see the first sentence of the abstract, for example) teaches that strength is an important requirement for a GDP. Because Herchen desires a high strength GDP, it would have been obvious to one skilled in the art to anneal a Si<sub>3</sub>N<sub>4</sub> or SiC GDP as taught by Aihara I, Aihara III and Takahashi to improve its strength. Furthermore, Takahashi teaches that the annealing step repairs surface cracks and scratches in a machined Si<sub>3</sub>N<sub>4</sub> or SiC part. Since Aihara I teaches that it is desirable to remove such cracks and scratches in a GDP, it would have been obvious to anneal a Si<sub>3</sub>N<sub>4</sub> GDP for this reason also. Regarding claim 18, it is noted that Aihara III (col. 4, lines 62-64) teaches that it is desirable to improve the dimensional accuracy of an annealed part by a 2nd machining step, and it would have been obvious to employ this further step when

Art Unit: 1763

producing a  $Si_3N_4$  GDP, for the desirable purpose of improving its dimensional accuracy.

Claims 1, 2, 4-7, 11, 18 and 43-45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Herchen (5,819,434) taken in view of Aihara I (6,258,440), taken in further view of Maydan or Wicker III (WO 98/14980) or Kim (6,041,733), and in further view of Aihara III (6,099,794) and Takahashi (JP 60-81076) for the reasons stated in the previous paragraph rejection, and taken in further view of Chen (5,824,605). Regarding the "drilled holes" recited in claim 1, Maydan (col. 2, lines 3-4) and Chen (col. 8, lines 8-17) teach that it was conventional in the prior art to drill the gas distribution holes in a ceramic GDP. It would have been obvious to one skilled in the art to drill Herchen's holes, because Maydan and Chen teach that it was known in the art to form GDP holes by drilling.

Claims 12-14, 18 and 40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Schneider (6,263,829) taken in view of Aihara I (6,258,440) or Aihara II (JP 10-167859). Schneider discloses a plasma-based fabrication apparatus having a plate shaped support 20 (Figs. 1-7) with gas distribution channels and orifices. The support 20 is properly considered a gas distribution plate, and it contains portions (insert 140) having a machined ceramic surface (col. 7, lines 10-51) in which insert 140 includes a drilled or machined orifice (col. 7, lines 49-51). Schneider teaches that it is more desirable to use monocrystalline ceramics for the insert 140 because polycrystalline ceramics cause more particulates in a plasma environment. Aihara, however, teaches that polycrystalline ceramics can be used for parts of a plasma

Art Unit: 1763

apparatus without causing undesirable particulate contamination, if the polycrystalline ceramic material is annealed after machining. It would have been obvious to one skilled in the art to modify the apparatus of Schneider by using annealed polycrystalline ceramic inserts 140 in Schneider's gas distribution plate 20, because Aihara teaches that such an annealed insert will accomplish Schneider's purpose of avoiding particulate contamination.

Claims 1, 2, 4-7, 11, 18 and 43-45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Schneider (6,263,829) taken in view of Aihara I (6,258,440) for the reasons discussed in the rejection of claims 12-14 and 40 in the preceeding paragraph, and taken in further view of Aihara III (6,099,794) and Takahashi (JP 60-81076). Schneider (col. 7, lines 13-20) teaches the use of Si<sub>3</sub>N<sub>4</sub> or SiC for his gas distribution plate. Regarding a step of annealing a Si<sub>3</sub>N<sub>4</sub> or SiC GDP, Aihara I (col. 4, lines 7-18) and Takahashi (see the English translation) teach that it is desirable to anneal a Si<sub>3</sub>N<sub>4</sub> or SiC article to improve its strength, and Aihara III (col. 4, lines 51-64) teaches that it is desirable to anneal a Si<sub>3</sub>N<sub>4</sub> article to improve its strength. It would have been obvious to one skilled in the art to anneal a GDP made of Si<sub>3</sub>N<sub>4</sub> or SiC as suggested by Schneider because strength is a desirable feature in any ceramic article. Furthermore, Takahashi teaches that the annealing step repairs surface cracks and scratches in a machined Si<sub>3</sub>N<sub>4</sub> part. Since Aihara I teaches that it is desirable to remove such cracks and scratches in a GDP in order to reduce particulate contamination, it would have been obvious to anneal a Si<sub>3</sub>N<sub>4</sub> GDP for this reason also. Regarding claim 18, it is noted that Aihara III (col. 4, lines 62-64) teaches that it is

Art Unit: 1763

desirable to improve the dimensional accuracy of an annealed part by a second machining step, and it would have been obvious to employ this further step when producing a Si<sub>3</sub>N<sub>4</sub> GDP, for the desirable purpose of improving its dimensional accuracy.

Claims 1, 2, 4-7, 11-14, 18, 40 and 43-45 are rejected under 35 U.S.C. 102(e) as anticipated by or, in the alternative, under 35 U.S.C. 103(a) as obvious over Wicker I (5,993,594). Wicker discloses a GDP made by hot pressing silicon nitride at a temperature above 1500° C (col. 7, lines 34-38). Wicker teaches (col. 3, lines 33-42) that his GDP results in much reduced particulate generation and much lower rate of chemical reaction with process gases. In view of the product-by-process nature of applicant's claims, the GDP of Wicker is prima facie not distinguishable from the presently claimed GDP.

Regarding the rejection of claim 12, applicants have argued that nothing in these references teaches or suggests annealing at a controlled temperature between about 1500° C to 1600° C for a time from about 5 to 10 hours. It is noted, however, that example 4 of Aihara I includes annealing at 1600° C for 3 hours, and example 6 includes annealing at 1700° C for 4 hours. Annealing time periods of 3 hours and 4 hours read on the claimed 'about 5 hours'. Also, the annealing temperatures of 1600° C and 1700° C read on the claimed 'about 1600° C'. More importantly, it is noted that the present claims are product claims, while the claim limitations pertaining to the duration and temperature of annealing are process limitations that do not so limit the claims.

Art Unit: 1763

Applicants have argued that Aihara I at col. 4, lines 8-18, teaches away from annealing bodies made of Si<sub>3</sub>N<sub>4</sub> or SiC. It is noted, however, that the passage of Aihara cited by applicants only teaches away from using Si<sub>3</sub>N<sub>4</sub> or SiC in an apparatus that uses the particular halogen based corrosive gases, which Aihara is concerned with. The other prior art of record teaches that a GDP constructed of Si<sub>3</sub>N<sub>4</sub> or SiC can be used in plasma processing apparatus using other types of gases.

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Richard Bueker whose telephone number is (571) 272-1431. The examiner can normally be reached on 9 AM - 5:30 PM, Monday-Friday.

Art Unit: 1763

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Gregory Mills can be reached on (571) 272-1439. The fax phone number for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 308-0661.

Rues Bul

Richard Bueker Primary Examiner Art Unit 1763